CAM-IP3138W-A-SI-28-AI

8MP AI Full Color Fixed Lens IP Turret



FEATURES

- 8MP, H.265, 24x7 full color
- 2.8mm Fixed Lens
- 0.007Lux@F1.0
- Smart Illumination
- Face detection
- Built-in Microphone
- 3DNR
- Micro SD up to 256G
- IP66, PoE, white

Specifications

Video	
Imaging Device	1/2.7"
Effective Pixels	8MP 3840（H）x 2160（V）
Scanning System	Progressive CMOS
Min. Illumination	Color 0.007lux @ F1.0(AGC ON) ; B/W 0 lux @ IR ON
Lens Type	
Focal Length (Zoom Ratio)	2.8 mm
Max. Aperture Ratio	F No. 1.0
Angular Field of View	Horizontal: 110°, Vertical: 57.5°, Diagonal: 131°
Min. Object Distance	1m
Lens Type	M12
Operational	
IR LED	2
WarmLight	2
IR Viewable Length	Up to 30m
WarmLight Viewable Length	Up to 30m
Type of complementary light	Default warm light, switchable infrared light
Backlight Compensation	Off/On (5 Zone)
Wide Dynamic Range	DWDR
Digital Noise Reduction	3D DNR
Motion Detection	Off/On (8 Level)
Image Setting	Full Color Mode/Day&Night Mode/Schedule
Privacy Masking	Off/On (4 Zone, Rectangle)

Gain Control	Auto
White Balance	Auto/Manual/Indoor
Electronic Shutter Speed	1/5 ~ 1/20000s
On-Board Storage	Micro SD slot, up to 256GB
Alarm	NA
Audio	Built-in microphone
Hardware Reset	Yes
Smart Feature	PID,LCD,PD/VD,SOD,CC,CD,QD,Heat MAP,RSD, FD （detection）
Network	
Ethernet	RJ45(10/100BASE-T)
Video Compression Format	H.265/H.264
Resolution	Mainstream@20fps 8MP(3840x2160),5MP(2880x1620),4MP(2592x1520) ,3MP(2304x1296),1080P(1920x1080),960P(1280*960),720P(1280x720) Substeam@20fps 720P(1280x720),VGA(640x480),QVGA(320x240) Mobilestream@20fps VGA(640x480), QVGA（320x240）
Video Quality Ajustment	256Kbps ~ 16Mbps
Bitrate control method	CBR/VBR
IP	IPv6
Protocol	TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP, SMTP,NTP,UPnP,SNMP,HTTPS,FTP
Security	IP address filter;complicated password;Authenticated username and password
Streaming Method	Unicast/Multicast
Application Programming Interface	ONVIF(Profile S/G/T)
Web Viewer	IE10/11 Safari V12.1 above Firefox V.52 above Google chrome V.57 above Edge V.79 above
Environmental	
Operating Conditions	-35 ~ +60°C/less than ≤ 95% RH
Ingress Protection	IP67
Electrical	
Input Voltage / Current	D12V/POE(IEEE802.3af)
Mechanical	
Material	Metal
Dimensions (HxWxD)	100*100*90mm
Weight	415g