CAM-IP3158W-180-PV-AI

4K Deterrence Panoramic IP Turret



FEATURES

- 8MP, H.265
- 2.0mm Fixed Lens
- Active Deterrence
- Built-in IR and warm light
- 180 degrees panoramic
- Built-in Microphone & Speaker
- Micro SD up to 256G
- IP67, PoE



ACC-BRK-W-B13W



ACC-BRK-B-B17W

Specifications

Imaging Device	1/2.8"
Effective Pixels	8MP 3840(H)×2160(V)
Scanning System	Progressive CMOS
Min. Illumination	Color 0.007lux @ F1.0(AGC ON) ; B/W 0 lux @ IR ON
Focal Length (Zoom Ratio)	2.0 mm
Max. Aperture Ratio	F No. 2.4
Angular Field of View	Horizontal: 180°；Vertical ：92°；Diagonal：180°
Lens Type	M12
IR LED	2
WarmLight	2
IR Viewable Length	Up to 25m
WarmLight Viewable Length	Up to 15m
Type of complementary light	Default warm light, switchable infrared light
Backlight Compensation	Off/On (5 Zone)
Wide Dynamic Range	Yes
Digital Noise Reduction	3D DNR
Motion Detection	Off/On (8 Level)
Image Setting	Day&Night Mode/Full Color Mode/Schedule
Privacy Masking	Off/On (4 Zone, Rectangle)
Gain Control	Auto

White Balance	Auto/Manual
Electronic Shutter Speed	1/5 ~ 1/20000s
On-Board Storage	Micro SD slot, up to 256GB
Alarm	Built-in red & blue flashing lights
Audio	Built-in microphone， speaker
Hardware Reset	Yes
Smart Feature	PID,LCD,PD/VD,SOD,CC,Heat MAP,RSD
Ethernet	RJ45(10/100BASE-T)
Video Compression Format	H.265/H.264
Resolution	Main Stream 8MP(3840x2160),5MP(2592x1944,3072x1728), 4MP(2592x1520),3MP(2304x1296),1080P(1920x1080), 960P(1280*960),720P(1280x720), Sub Steam 720P(1280x720),VGA(640x480),QVGA(320x240) Mobile Stream VGA(640x480), QVGA（320x240）
Video Quality Ajustment	256Kbps ~ 16Mbps
Bitrate control method	CBR/VBR
Streaming Capability	Triple-Stream(Main/Sub/Mobile)
IP	IPv4/IPv6
Protocol	TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP, SMTP,NTP,UPnP,SNMP,HTTPS,FTP
Security	IP address filter;complicated password;Authenticated username and password
Streaming Method	Unicast/Multicast
Application Programming Interface	ONVIF(Profile S/G/T)
Web Viewer	IE10/11, Safari V12.1 above, Firefox V.52 above, Google chrome V.57 above, Edge V.79 above
Operating Conditions	-35～+60°C/less than ≤ 95% RH
Ingress Protection	IP67
Input Voltage / Current	D12V/POE(IEEE802.3af)
Material	Metal