CAM-IP3765W-0550-LPR

5MP License Plate Recognition Motorized Lens IP Bullet



FEATURES

- 5MP, H.265
- 5-50mm motorized Lens
- 0.003Lux@F1.6
- License plate recognition
- IR 80m
- Micro SD up to 256G
- IP67, PoE, white

Specifications

Video	
Imaging Device	1/2.7"
Effective Pixels	5MP Resolution
Scanning System	Progressive CMOS
Min. Illumination	Color 0.003lux @ F1.6(AGC ON) ; B/W 0 lux @ IR ON
Lens Type	
Focal Length (Zoom Ratio)	5-50mm
Max. Aperture Ratio	F No. 2.0
Angular Field of View	Horizontal:45°, Vertical:33°, Diagonal: 58°
Min. Object Distance	0.2m
Lens Type	motorized
Operational	
IR LED	1
IR Viewable Length	Up to 80m
Type of complementary light	Switchable infrared light
Wide Dynamic Range	WDR
Digital Noise Reduction	3D DNR
Motion Detection	Off/On (8 Level)
Privacy masking	Off/On(4 Zone, rectangle)

White Balance	Auto/Manual
Electronic Shutter Speed	1/5 ~ 1/20000s
On-Board Storage	Micro SD slot, up to 256GB
Alarm	1 input/1 output
Audio	1 input RCA/1 output RCA
Hardware Reset	Yes
Smart Feature	FR/PDVD/PID/LC/CC/HM/LPR/
Network	
Ethernet	RJ45(10/100BASE-T)
Video Compression Format	H.265/H.264
Resolution	Main Stream@20fps 8MP(3840x2160) Sub Stream@30fps 1080P(1920x1080),720P(1280x720),VGA(640x480),QVGA(320x240) Mobile Stream@30fps VGA(640x480), QVGA（320x240）
Video Quality Ajustment	256Kbps ~ 8Mbps
Bitrate control method	CBR/VBR
Protocol	TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP, SMTP,NTP,HTTPS
Security	IP address filter;complicated password;Authenticated username and password
Application Programming Interface	ONVIF profile s/g/t/m
Web Viewer	IE10/11
Environmental	
Operating Conditions	-30 ~ +60°C/less than ⩽ 95% RH
Ingress Protection	IP67
Electrical	
Input Voltage / Current	D12V/POE(IEEE802.3af)
Mechanical	
Material	Metal
Dimensions (HxWxD)	108*301.11mm