XVR-3108-AI

8 channel 8MP Digital Video Recorder



FEATURES

- TVI/CVI/AHD/Analog/IP Auto Detect
- 4K, 8CH, AI XVR
- 4K Recording
- 4K HDMI, BNC Spot Output
- 1 SATA port, up to 16TB HDD
- 8CH Simultaneous Playback

Specifications

Video		
Inputs		32Mbps ~96Mbps
Outputs		96Mbps
Analog video-input		8CH inputs
IP Video Input		4ch,(only IP up to 6ch)
Composite Video Input		up to 12ch (Analog video + IP video)
Performance		
Recording and Playback	Compression	Audio: G.711a Video : H.264/H.265
	Display resolution	Analog : 8MP(15fps),5MP(20fps), 4MP/1080P/720P/960H (30fps) IP: 4K/4MP/1080P/720P Single IP channel preview up to 4K@30 fps
	Speed	**Main-stream** Analog :8MP:10fps(each ch),5MP:14fps(each ch),4MP:18fps(each ch), 1080P:PAL:25fps(each ch), NTSC:30fps(each ch), IP: PAL:25fps(each ch)/NTSC: 30fps(each ch) **Sub-stream** PAL: 704*576:10fps(each ch) NTSC: 704*480:10fps(each ch)
	AI	PID - Perimeter Intrusion Detection LCD - Line Crossing Detection PD&VD - Human&Vehicle Detection FD - Face Detection

Recording and Playback	Event	MD(Sensitivity Level 1~8)
		Video loss
		Beep, Email, Push notification to Mobile APP
	Playback function	Fast forward / backward (2x, 4x, 8x,16x)
		Slow forward (1/2x, 1/4x, 1/8x,1/16x)
	Playback	8MP: 72fps (Max 8CH playback) 5MP: 112fps(Max 8CH playback) 4MP: 144fps (Max 8CH playback) 1080P: 240fps (Max 8CH playback)
	Local	UI5.0
	WEB	IE10/11 Safari V12.1 above Firefox V.52 above Google chrome V.57 above Edge V.79 above
	Mobile viewer	Rxcamview
	Push N/Atification	Yes
P/W Reset		Factory Reset : Press 10 seconds
Monitors	BNC	1 (704*576)
	VGA	1（1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080）
	HDMI	1(1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080 , 2560*1440, 3840*2160/EDID)
	Ethernet	1 RJ45 10/100 Base-T
	USB	USB2.0*1(front) USB2.0*1(rear)
	Audio	4 in / 1 out
	Storage	1 SATA HDD, up to 16TB, (Surveillance Grade)
	RS485	1
General		
OSD Language		English/French/Spanish/Portuguese/German/Italian/ Greek/Danish/Finnish/Russia/Hebrew/Turkish/Bulgarian/ Arabic/Korean/Japanese/Thai/Hindi/Romanian/Dutch/ Polish
Mechanical design	Dimension (WxDxH)	300X227X53mm
Electrical	Input Voltage/Current	12V/2A
	Power consumption (excluding hard disk)	4.7W
Environmental	Operating Temperature/ Humidity	Temperature : -10°C~+50°C (14°F ~ 122°F) Humidity : Less than 90%RH